

Item	Dial Size (mm.)	Range	Connection	Burdon Mat.	Model	Qty.
1	40mm.	0 - 10kgf/cm2 (PSI)	R1/8" Bottom	Brass	GK20-161	107
2	40mm.	0 - 2kgf/cm2 (PSI)	R1/8" Bottom	Brass	GK20-161	89
3	40mm.	0 - 4 Kg/cm2 (PSI)	R1/8" Bottom	Brass	GK20-161	69
4	40mm.	0 - 2bar	1/8"NPT Back	Brass	GK25-111	5
5	40mm.	0 - 7bar	1/8"NPT Back	Brass	GK25-111	20
6	50mm.	0 - 7kgf/cm2 (PSI)	R1/4" Bottom	Brass	GK20-271	15
7	50mm.	0-4KG/PSI	R1/4" Back	Brass	GK25-271	27
8	50mm.	0-7KG/PSI	R1/4" Back	Brass	GK25-271	90
9	60mm.	0 - 10 Kg/Cm2	R1/4" Bottom	Brass	AA10-171	1
10	60mm.	0 -3Bar	R1/4" Bottom	Brass	BA10-171	4
11	60mm.	76cmHg-4kgf/cm2	R1/4" Back	SUS316	BA15-273	1
12	60mm.	0-15kgf/cm2(PSI)	R1/4" Bottom	SUS316	GV50-273	26
13	75mm.	0-15 kgf/cm2(PSI)	R3/8" Bottom	Brass	AC10-281	1
14	75mm.	0-2 kgf/cm2	R3/8" Bottom	Brass	AC10-281	4
15	75mm.	0-2 kgf/cm2 (PSI)	R3/8" Bottom	Brass	AC10-281	5
16	75mm.	0-250kgf/cm2	R3/8" Back	Brass	AC15-181	3
17	75mm.	0-4 kgf/cm2 (PSI)	R3/8" Back	Brass	AC15-181	6
18	75mm.	0-6kgf/cm2(PSI)	R3/8" Back	Brass	AC15-181	2
19	75mm.	0-76cmHg	R3/8" Bottom	Brass	BC12-181	6
20	75mm.	0 -6kgf/cm2	R3/8" Back	Brass	BC15-181	5
21	100mm.	-76 cmHg-35 kgf/cm2	R1/4" Bottom	Brass	AE10-171	2
22	100mm.	0-30kgf/cm2	G3/8" Bottom	Brass	AE10-131	1
23	100mm.	0-4kgf/cm2	G3/8" Bottom	Brass	AE10-131	6
24	100mm.	0 - 150 PSI	R1/2" Bottom	Brass	AE10-191	2
25	100mm.	0-15PSI	R1/2" Bottom	Brass	AE10-191	1
26	100mm.	0-200PSI	R1/2" Bottom	Brass	AE10-191	8
27	100mm.	760mmHg-1kg/cm2	R1/2" Bottom	Brass	AE10-191	2
28	100mm.	-760mmHg-35kg/cm2	G3/8" Bottom	Brass	AE10-231	5
29	100mm.	-76cmHg-20kg/cm2	G3/8" Bottom	Brass	AE10-231	6
30	100mm.	76cmHg-35kg/cm2	G3/8" Bottom	Brass	AE10-231	4
31	100mm.	-76cmHg-35kgf/cm2	G3/8" Bottom	Brass	AE10-231-HV	6
32	100mm.	-76cmHg-35kgf/cm2	G3/8" Bottom	Brass	AE10-231-MV	5
33	100mm.	0 -100kgf/cm2	G3/8" Bottom	Brass	AE10-231-V	4
34	100mm.	0 -5kgf/cm2	G3/8" Bottom	Brass	AE10-231-V	1
35	100mm.	0-3kgf/cm2	G1/2" Bottom	Brass	AE10-241	21
36	100mm.	0-100kg	R3/8" Bottom	Brass	AE10-281	1
37	100mm.	0-100kgf/PSI	R3/8" Bottom	Brass	AE10-281	8
38	100mm.	0 - 20kgf/PSI	R3/8" Bottom	Brass	AE10-281	14
39	100mm.	0-25kgf/cm2(PSI)	R3/8" Bottom	Brass	AE10-281	14
40	100mm.	0-2kgf/cm2(PSI)	R3/8" Bottom	Brass	AE10-281	14
41	100mm.	0-35kgf/cm2(PSI)	R3/8" Bottom	Brass	AE10-281	5
42	100mm.	0-4kgf/cm2(PSI)	R3/8" Bottom	Brass	AE10-281	5
43	100mm.	0-60PSI	R3/8" Bottom	Brass	AE10-281	1
44	100mm.	0-100KG	R1/2" Bottom	Brass	AE10-291	1
45	100mm.	0-1kg/cm2	R1/2" Bottom	Brass	AE10-291	1
46	100mm.	0 - 1kg/PSI	R1/2" Bottom	Brass	AE10-291	2
47	100mm.	0-200kgf/PSI	R1/2" Bottom	Brass	AE10-291	5
48	100mm.	0-25bar	R1/2" Bottom	Brass	AE10-291	5
49	100mm.	0-25kg/PSI	R1/2" Bottom	Brass	AE10-291	33
50	100mm.	0-2kgf	R1/2" Bottom	Brass	AE10-291	1
51	100mm.	0-2kgf/PSI	R1/2" Bottom	Brass	AE10-291	19
52	100mm.	0-4kg	R1/2" Bottom	Brass	AE10-291	1
53	100mm.	0-100kgf/cm2 (PSI)	R1/2" Bottom	SUS316	AE10-293	3
54	100mm.	0-16kgf	R1/2" Bottom	SUS316	AE10-293	13
55	100mm.	0 - 40kgf/cm2(PSI)	R1/2" Bottom	SUS316	AE10-293	1
56	100mm.	0-6kg	R1/2" Bottom	SUS316	AE10-293	1
57	100mm.	0-6kgf/PSI	R1/2" Bottom	SUS316	AE10-293	2
58	100mm.	0-100PSI	G3/8" Back	Brass	AE15-131	4
59	100mm.	0-6kg/cm2	G3/8" Back	Brass	AE15-131	1
60	100mm.	0-6kgf/cm2	G3/8" Back	SUS316	AE15-133	2
61	100mm.	0-15bar	G1/2" Back	Brass	AE15-141	1

Item	Dial Size (mm.)	Range	Connection	Burdon Mat.	Model	Qty.
62	100mm.	0-100kgf/PSI	R3/8" Back	Brass	AE15-181	3
63	100mm.	0-20kgf/cm2(PSI)	R3/8" Back	Brass	AE15-181	5
64	100mm.	0-4kgf/cm2	R3/8" Back	Brass	AE15-181	5
65	100mm.	0-4kgf/cm2(PSI)	R3/8" Back	Brass	AE15-181	12
66	100mm.	0-2kgf/PSI	R1/2" Back	Brass	AE15-191	6
67	100mm.	0-350kg/PSI	R1/2" Back	Brass	AE15-191	4
68	100mm.	0-4kg (PSI)	R1/2" Back	Brass	AE15-191	5
69	100mm.	0-6kg (PSI)	R1/2" Back	Brass	AE15-191	16
70	100mm.	760mmHg-0mmHg(Vacum G	R1/2" Back	Brass	AE15-191	3
71	100mm.	0-100PSI	G3/8" Back	Brass	AE15-231	2
72	100mm.	0-10kgf/cm2	G3/8" Back	SUS316	AE15-233	3
73	100mm.	0-100kg/cm2	R3/8" Back	Brass	AE15-281	1
74	100mm.	0-15kgf/PSI	R3/8" Back	Brass	AE15-281	6
75	100mm.	0-20kgf/cm2(PSI)	R3/8" Back	Brass	AE15-281	6
76	100mm.	0-4kg/PSI	R3/8" Back	Brass	AE15-281	2
77	100mm.	0-760mmHG	R1/2" Back	Brass	AE15-291	5
78	100mm.	0- 300 PSI/30inHg	G3/8" Bottom	Brass	BE10-131	1
79	100mm.	0- 4kg	G3/8" Bottom	SUS316	BE10-133	3
80	100mm.	760mmHg-20kg	G3/8" Bottom	SUS316	BE10-133	1
81	100mm.	760mmHg-6kg	G3/8" Bottom	SUS316	BE10-133	1
82	100mm.	-760mmHg-6 Kg/cm2	G3/8" Bottom	SUS316	BE10-133	2
83	100mm.	0-15bar(PSI)	G1/2" Bottom	Brass	BE10-141	3
84	100mm.	0-20bar/PSI	G1/2" Bottom	Brass	BE10-141	4
85	100mm.	0- 15kg	R3/8" Bottom	Brass	BE10-181	1
86	100mm.	0-2kg/cm2	R3/8" Bottom	Brass	BE10-281	3
87	100mm.	0-35kg(PSI)	R1/2" Bottom	Brass	BE10-291	1
88	100mm.	0-5kg/cm2	R1/2" Bottom	Brass	BE10-291	3
89	100mm.	0-760mmHg	R1/2" Bottom	Brass	BE10-291	12
90	100mm.	0-1kg/cm2	R1/2" Bottom	SUS316	BE10-293	5
91	100mm.	0-4kg/cm2(PSI)	R1/2" Bottom	SUS316	BE10-293	6
92	100mm.	0- 50kg/cm2	R1/2" Bottom	SUS316	BE10-293	2
93	100mm.	0-60kg/cm2(PSI)	R1/2" Bottom	SUS316	BE10-293	1
94	100mm.	0-70kg/cm2(PSI)	R1/2" Bottom	SUS316	BE10-293	5
95	100mm.	-1-1bar	G1/2" Bottom	Brass	BE12-141	1
96	100mm.	0-30kg/cm2	G1/2" Bottom	SUS316	BE12-142	2
97	100mm.	0-1000PSI	G1/2" Bottom	SUS316	BE12-143	5
98	100mm.	0-6PSI	G1/2" Bottom	SUS316	BE12-143	3
99	100mm.	76cmHg-1kgf/cm2	R3/8" Bottom	SUS316	BE12-183	2
100	100mm.	0-25bar	R1/2" Bottom	Brass	BE12-191	3
101	100mm.	760MMHG-1KG	R1/2" Bottom	Brass	BE12-191	1
102	100mm.	0-3kgf/cm2	R1/2" Bottom	SUS316	BE12-193	1
103	100mm.	760mmHg-2kg	R1/2" Bottom	SUS316	BE12-193	11
104	100mm.	0-20kg/cm2	G3/8" Bottom	SUS316	BE12-233	4
105	100mm.	0-35kgf/cm2	G3/8" Bottom	SUS316	BE12-233	5
106	100mm.	0-3kgf/cm2	G3/8" Bottom	SUS316	BE12-233	3
107	100mm.	-76cmHg-4kgf/cm2	G3/8" Bottom	SUS316	BE12-233	3
108	100mm.	0-20kgf/cm2	G1/2" Bottom	Brass	BE12-241	10
109	100mm.	0-25kgf/cm2	G1/2" Bottom	Brass	BE12-241	8
110	100mm.	0-35kgf/cm2	G1/2" Bottom	Brass	BE12-241	10
111	100mm.	0-200PSI	G1/2" Bottom	SUS316	BE12-243	2
112	100mm.	0-3kg	G1/2" Bottom	SUS316	BE12-243	5
113	100mm.	0-100bar	1/2" NPT Bottom	SUS316	BE12-263	18
114	100mm.	0-25bar	1/2" NPT Bottom	SUS316	BE12-263	8
115	100mm.	0-30bar	1/2" NPT Bottom	SUS316	BE12-263	7
116	100mm.	0-40bar	1/2" NPT Bottom	SUS316	BE12-263	9
117	100mm.	0-4bar	1/2" NPT Bottom	SUS316	BE12-263	26
118	100mm.	0-4kg/cm2	1/2" NPT Bottom	SUS316	BE12-263	1
119	100mm.	0-60bar	1/2" NPT Bottom	SUS316	BE12-263	17
120	100mm.	0-70bar	1/2" NPT Bottom	SUS316	BE12-263	10
121	100mm.	0-2kgf/cm2(PSI)	R3/8" Bottom	Brass	BE12-281	5
122	100mm.	0-10bar	R3/8" Bottom	SUS316	BE12-283	1

Item	Dial Size (mm.)	Range	Connection	Burdon Mat.	Model	Qty.
123	100mm.	0-1kg/cm2(PSI)	R3/8" Bottom	SUS316	BE12-283	7
124	100mm.	0-20kgf/cm2	R3/8" Bottom	SUS316	BE12-283	5
125	100mm.	0-25kgf/cm2	R3/8" Bottom	SUS316	BE12-283	11
126	100mm.	0-3kg/cm2	R3/8" Bottom	SUS316	BE12-283	5
127	100mm.	0-3kg/cm2(PSI)	R3/8" Bottom	SUS316	BE12-283	8
128	100mm.	0-4kg/cm2(PSI)	R3/8" Bottom	SUS316	BE12-283	5
129	100mm.	760cmHg-4kgf/cm2	R3/8" Bottom	SUS316	BE12-283	3
130	100mm.	76cmHg-6kgf/cm2	R3/8" Bottom	SUS316	BE12-283	1
131	100mm.	0-100PSI	R1/2" Bottom	Brass	BE12-291	4
132	100mm.	0-30PSI(inHg)	R1/2" Bottom	Brass	BE12-291	2
133	100mm.	0-100kgf/cm2	R1/2" Bottom	SUS316	BE12-293	12
134	100mm.	0-100kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	4
135	100mm.	0-100PSI	R1/2" Bottom	SUS316	BE12-293	14
136	100mm.	0-14bar	R1/2" Bottom	SUS316	BE12-293	10
137	100mm.	0-150PSI	R1/2" Bottom	SUS316	BE12-293	1
138	100mm.	0-150kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	5
139	100mm.	0-15bar	R1/2" Bottom	SUS316	BE12-293	1
140	100mm.	0-15kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	2
141	100mm.	0-16bar	R1/2" Bottom	SUS316	BE12-293	2
142	100mm.	0-16bar(PSI)	R1/2" Bottom	SUS316	BE12-293	4
143	100mm.	0-1bar	R1/2" Bottom	SUS316	BE12-293	8
144	100mm.	0-1bar(PSI)	R1/2" Bottom	SUS316	BE12-293	8
145	100mm.	0-1kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	15
146	100mm.	0-200PSI	R1/2" Bottom	SUS316	BE12-293	1
147	100mm.	0-20bar	R1/2" Bottom	SUS316	BE12-293	3
148	100mm.	0-20kgf/cm2	R1/2" Bottom	SUS316	BE12-293	2
149	100mm.	0-25bar	R1/2" Bottom	SUS316	BE12-293	7
150	100mm.	0-25bar/PSI	R1/2" Bottom	SUS316	BE12-293	2
151	100mm.	0-25kgf/cm2	R1/2" Bottom	SUS316	BE12-293	14
152	100mm.	0-2bar	R1/2" Bottom	SUS316	BE12-293	20
153	100mm.	0-2bar(PSI)	R1/2" Bottom	SUS316	BE12-293	5
154	100mm.	0-2kgf/cm2	R1/2" Bottom	SUS316	BE12-293	10
155	100mm.	0-35bar	R1/2" Bottom	SUS316	BE12-293	5
156	100mm.	0-35kgf/cm2	R1/2" Bottom	SUS316	BE12-293	5
157	100mm.	0-35kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	8
158	100mm.	0-3bar	R1/2" Bottom	SUS316	BE12-293	12
159	100mm.	0-3bar/PSI	R1/2" Bottom	SUS316	BE12-293	5
160	100mm.	0-40kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	23
161	100mm.	0-4bar	R1/2" Bottom	SUS316	BE12-293	14
162	100mm.	0-4kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	20
163	100mm.	0-50bar	R1/2" Bottom	SUS316	BE12-293	5
164	100mm.	0-50kg	R1/2" Bottom	SUS316	BE12-293	4
165	100mm.	0-50kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	7
166	100mm.	0-5bar	R1/2" Bottom	SUS316	BE12-293	2
167	100mm.	0-5bar(PSI)	R1/2" Bottom	SUS316	BE12-293	10
168	100mm.	0-5kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	12
169	100mm.	0-60bar/PSI	R1/2" Bottom	SUS316	BE12-293	9
170	100mm.	0-60kg/cm2	R1/2" Bottom	SUS316	BE12-293	1
171	100mm.	0-60kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	13
172	100mm.	0-60PSI	R1/2" Bottom	SUS316	BE12-293	9
173	100mm.	0-6bar(PSI)	R1/2" Bottom	SUS316	BE12-293	5
174	100mm.	0-6kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	2
175	100mm.	0-70kgf/cm2	R1/2" Bottom	SUS316	BE12-293	12
176	100mm.	0-70kgf/cm2 (PSI)	R1/2" Bottom	SUS316	BE12-293	16
177	100mm.	0-760mmHg	R1/2" Bottom	SUS316	BE12-293	5
178	100mm.	760mmHg-15kg/cm2	R1/2" Bottom	SUS316	BE12-293	11
179	100mm.	760mmHg-1kg/cm2	R1/2" Bottom	SUS316	BE12-293	27
180	100mm.	76mmHg-2kg/cm2	R1/2" Bottom	SUS316	BE12-293	8
181	100mm.	760mmHg-4kg/cm2	R1/2" Bottom	SUS316	BE12-293	6
182	100mm.	760mmHg-5kg/cm2	R1/2" Bottom	SUS316	BE12-293	14
183	100mm.	76cmHg-10kg/cm2	R1/2" Bottom	SUS316	BE12-293	3

Item	Dial Size (mm.)	Range	Connection	Burdon Mat.	Model	Qty.
184	100mm.	76cmHg-2kg/cm2	R1/2" Bottom	SUS316	BE12-293	4
185	100mm.	76cmHg-6kg/cm2	R1/2" Bottom	SUS316	BE12-293	2
186	100mm.	76cmHg-15kg/cm2	R3/8" Back	SUS316	BE15-183	4
187	100mm.	76cmHg-35kg/cm2	R3/8" Back	SUS316	BE15-183	7
188	100mm.	76cmHg-15kgf/cm2	1/2"NPT Back	SUS316	BE17-263	6
189	100mm.	76cmHg-35kg/cm2	1/2"NPT Back	SUS316	BE17-263	4
190	100mm.	0-20kg/cm2	1/2"NPT Bottom	SUS316	GV42-163	5
191	100mm.	0-2mPA	1/2"NPT Bottom	SUS316	GV42-163	1
192	100mm.	0-4kg/PSI	1/2"NPT Bottom	SUS316	GV42-163	10
193	100mm.	0-10MPa (kg/cm2)	R3/8" Bottom	SUS316	GV42-183	2
194	100mm.	0-1MPa/10kg	R3/8" Bottom	SUS316	GV42-183	2
195	100mm.	0-35kg/cm2	R1/2" Bottom	SUS316	GV42-193	1
196	100mm.	0-60kgf/cm2	1/4"NPT Bottom	SUS316	GV42-253	1
197	100mm.	0-60bar	1/2"NPT Bottom	SUS316	GV42-263	2
198	100mm.	0-20kgf/cm2 (PSI)	R3/8" Bottom	SUS316	GV42-283	9
199	100mm.	0-15barl	R1/2" Bottom	SUS316	GV42-293	1
200	100mm.	0-20bar	R1/2" Bottom	SUS316	GV42-293	1
201	100mm.	0-2bar	R1/2" Bottom	SUS316	GV42-293	15
202	100mm.	0-35bar	R1/2" Bottom	SUS316	GV42-293	16
203	100mm.	0-40bar	R1/2" Bottom	SUS316	GV42-293	26
204	100mm.	0-4bar(PSI)	R1/2" Bottom	SUS316	GV42-293	7
205	100mm.	0-4kgf/cm2	R1/2" Bottom	SUS316	GV42-293	10
206	100mm.	0-5bar	R1/2" Bottom	SUS316	GV42-293	8
207	100mm.	0-60kg	R1/2" Bottom	SUS316	GV42-293	5
208	100mm.	0-60kg (PSI)	R1/2" Bottom	SUS316	GV42-293	5
209	100mm.	0-70Bar	R1/2" Bottom	SUS316	GV42-293	15
210	100mm.	-1-1bar	R1/2" Bottom	SUS316	GV42-293	2
211	100mm.	760mmHg-1bar	R1/2" Bottom	SUS316	GV42-293	4
212	100mm.	0-10kgf/cm2	G3/8" Back	SUS316	GV47-133	3
213	100mm.	0 - 20 bar	G3/8" Back	SUS316	GV47-133	1
214	100mm.	0 - 20 kg/PSI	G3/8" Back	SUS316	GV47-133	1
215	100mm.	0 - 60 bar	1/2"NPT Back	SUS316	GV47-163	1
216	150mm.	0-250Bar	G3/8" Bottom	Brass	AG10-131	1
217	150mm.	0-250Bar	G1/2" Bottom	Brass	AG10-141	2
218	150mm.	0-760mmHg	R1/2" Bottom	Brass	AG10-191	1
219	150mm.	0-25KG	1/2" NPT Bottom	Brass	AG10-261	3
220	150mm.	0-60PSI	R3/8" Bottom	Brass	AG10-281	2
221	150mm.	0-350kgf/cm2	G 3/8' Back	Brass	AG15-131	3
222	150mm.	0-350PSI	G 3/8' Back	Brass	AG15-131	4
223	150mm.	0-25BAR	R1/2" Bottom	Brass	BG10-191	1
224	150mm.	0-50kg	R1/2" Bottom	Brass	BG10-191	1
225	150mm.	0-3000 PSI	R1/2" Bottom	SUS316	BG10-193	1
226	150mm.	0-15inHg	G3/8" Bottom	Brass	BG10-231	4
227	150mm.	0-10kg/cm2	1/2" NPT Bottom	Brass	BG10-261	4
228	150mm.	0-10KG	R1/2" Bottom	Brass	BG10-291	1
229	150mm.	0-2000 MMH20	G3/8" Bottom	SUS316L	GL21-233	4
230	150mm.	0-25bar	1/2"NPT Bottom	SUS316	GV44-163	2
231	150mm.	0-10kg/cm2	G1/2"Bottom	Brass	JM21-241	2
232	150mm.	0-6 BAR	G1/2"Bottom	Brass	JM21-241	1
233	200mm.	0 - 0.1 MPA	R1/2" Back	Brass	AJ15-191	2
234	200mm.	0-10KG	G1/2" Bottom	SUS316	DG57-243	1

Item	Dial Size (mm.)	Range	Connection	Burdon Mat.	Model	Qty.	More description
235	60mm.	0-50Deg.C.	R1/2" Bottom	SUS304	TB22-000	1	Bulb Length x Bulb Dia : 110mm. x 10mm.
236	75mm.	0-120 Deg.C.	R1/2" Back	SUS304	TB13-000	4	Bulb Length x Bulb Dia : 180mm. x 10 mm.
237	75mm.	0-120 Deg.C.	R1/2" Back	SUS304	TB13-000	2	Bulb Length x Bulb Dia : 210mm. x 10 mm.
238	100mm.	0-100Deg.C.	R1/2" Back	SUS304	TB14-000	1	Bulb Length x Bulb Dia : 150mm. x 8 mm.
239	100mm.	0-150Deg.C.	R1/2" Back	SUS304	TB14-000	2	Bulb Length x Bulb Dia : 150mm. x 8 mm.
240	100mm.	0-150 Deg.C.	R1/2" Back	SUS304	TB14-000	6	Bulb Length x Bulb Dia : 200 mm. x 8 mm.
241	100mm.	0-150 Deg.C.	R1/2" Back	SUS304	TB14-000	2	Bulb Length x Bulb Dia : 210mm. x 8 mm.
242	100mm.	0-150 Deg.C.	R1/2" Back	SUS304	TB14-000	10	Bulb Length x Buld Dia : 500mm. x 8 mm.
243	100mm.	0-200 Deg.C.	R1/2" Back	SUS304	TB14-000	12	Bulb Length x Bulb Dia : 100mm. x 8 mm.
244	100mm.	0-200 Deg.C.	R1/2" Back	SUS304	TB14-000	11	Bulb Length x Buld Dia : 200mm. x 8 mm.
245	100mm.	0-200 Deg.C.	R1/2" Back	SUS304	TB14-000	4	Bulb Length x Bulb Dia : 210mm. x 8 mm.
246	100mm.	0-300Deg.C.	R1/2" Back	SUS304	TB14-000	2	Bulb Length x Bulb Dia : 210mm. x 8 mm.
247	100mm.	0-120Deg.C.	R3/8" Back	SUS304	TB14-00B	9	Bulb Length x Bulb Dia : 60mm. x 6 mm.
248	100mm.	0-50 Deg.C.	JIS10K20ARF	SUS304	TB14-105	1	Bulb Length x Bulb Dia : 250mm. x 10 mm.
249	100mm.	0-100 Deg.C.	R1/2" Bottom	SUS304	TB24-000	6	Bulb Length x Bulb Dia : 100mm. x 8mm.
250	100mm.	0-300 Deg.C.	R1/2" Bottom	SUS304	TB24-000	1	Bulb Length x Bulb Dia : 60mm. x10 mm.
251	100mm.	0-100 Deg.C.	R1/2"	SUS304	TE54-000	4	Bulb Length x Bulb Dia : 250mm. x 10mm. Capillary 3 m
252	100mm.	0-300 Deg.C.	R1/2"	SUS304	TL64-000	3	Bulb Length x Bulb Dia : 50mm. x 15 mm. Capillary 3 m
253	100mm.	0-100Deg.C.	R1/2" Back	SUS304	TB14-000	4	Bulb Length x Bulb Dia : 150mm. x 8 mm.
254	100mm.	0-150 Deg.C.	R1/2" Back	SUS304	TB14-000	1	Bulb Length x Bulb Dia : 100mm. x 10 mm.
255	100mm.	0-200 Deg.C.	R1/2" Back	SUS304	TB14-000	2	Bulb Length x Bulb Dia : 120mm. x 10 mm.
256	100mm.	0-200 Deg.C.	R1/2" Back	SUS304	TB14-000	2	Bulb Length x Buld Dia : 210mm. x 8 mm.
257	100mm.	30-110 Deg.F.	R1/2" Back	SUS304	TB14-000	1	Bulb Length x Bulb Dia : 350mm. x 8 mm.
258	100mm.	30-210 Deg.F.	R1/2" Back	SUS304	TB14-000	2	Bulb Length x Bulb Dia : 350mm. x 8 mm.
259	100mm.	0-150 Deg.C.(32-300 Deg F.)	R1/2" Back	SUS304	TB14-000	5	Bulb Length x Bulb Dia : 180mm. x 8 mm.
260	100mm.	0-100 Deg.C.	1/2 PT (Bottom)	SUS304	TB24-000	2	Bulb Length x Bulb Dia : 100mm. x 10 mm.
261	100mm.	0-100 Deg.C.	R1/2" Bottom	SUS304	TB24-000	2	Bulb Length x Bulb Dia : 150mm. x 10 mm.
262	100mm.	0-100 Deg.C.	R1/2" Bottom	SUS304	TB24-000	1	Bulb Length x Bulb Dia : 190mm. x 10mm.
263	100mm.	0-200Deg.C.	R1/2" Bottom	SUS304	TB24-000	1	Bulb Length x Bulb Dia : 100mm. x 10 mm.
264	100mm.	0-60 Deg.C.(32-140 Deg F)	R1/2" Back	SUS304	TL14-000	1	Bulb Length x Bulb Dia : 120mm. x 10 mm.
265	150mm.	0-400Deg.C.	R1/2" Bottom	SUS304	TB26-000	3	Bulb Length x Bulb Dia : 400mm. x 10 mm.
266	150mm.	0-50 Deg.C.	1/2 PT (Back)	SUS304	TL56-000	4	Bulb Length x Bulb Dia : 300mm. x 10 mm. Capillary 1 m